



PATIO & PAVING

FOND DU LAC STEPPERS

GEOLOGY: dolomitic limestone

BASIC USE

on patios and walkways; stone is dryset in gravel (screenings) bed or mortared in

COLOR RANGE

gray, light gray, buff, and white

COLOR CONSISTENCY PER PALLET

somewhat consistent

WEIGHT CALCULATED IN INCHES

$l \times w \times h / 1728$ (inches cubed) $\times 170$
= approx 170 pounds per cubic foot

PALLET

4,000 pounds

PATIO & PAVING

COMMON COVERAGE *Est.(can vary)

1" to 2" height 1-3/4" to 2-1/2"
80 square feet / ton 65 ft²/ton

FOND DU LAC STEPPERS

DIMENSIONS

US: inches

l: 8" to 24"

h: 1" to 2" or

h: 1-3/4" to 2-1/2"

w: 8" to 24"

note: lengths and widths are irregular shapes

8 inches to 24 inches in diameter

METRIC: mm

l: 203 to 609 mm

h: 25 to 51 mm or

h: 44 to 63 mm

w: 203 to 609 mm

PART NUMBERS

part no. 1" to 2": 1PATBUE02015TN

part no. 1-3/4" to 2-1/2": 1PATBUE02017TN

PATIO & PAVING

FOND DU LAC STEPPERS

TYPICAL PIECE

ends irregular;

natural cleft top and bottom;

natural split sides;

stone is random shapes

ASTM TESTING DATA

FOND DU LAC C97 water absorption—0.36%

FOND DU LAC C97 density—174.2 pcf

FOND DU LAC C99

modulus of rupture—1,470 psi

FOND DU LAC C170

compressive strength w/rift—29,040 psi

compressive strength across rift—34,240 psi

FOND DU LAC C880

flexural strength—1,740 psi



www.buechelstone.com