



**PANEL INSTALLATION SHOWN**

Mortar: Western Type- S  
 Joint Type: raked  
 Size- 11 5/8" x 23 5/8" thermalled finish

**COMMON APPLICATIONS**

- MILL CREEK
- ACCESSORIES \_\_\_\_\_  
(e.g. quoins, keystones, light mounts)
- DOOR & WINDOW SURROUNDS \_\_\_\_\_
- FIREPLACE SURROUNDS \_\_\_\_\_
- HEARTHS & MANTELS \_\_\_\_\_
- PIER CAPS \_\_\_\_\_
- SILLS \_\_\_\_\_



**CUT STONE**  
**MILL CREEK**  
**PANELS, CUT STONE**  
**& SLABS**

**GEOLOGY:** dolomitic limestone - quarried in USA

**COLOR RANGE**  
 light buff to light gray, mottled- may have shades of pink when thermalled

**COLOR CONSISTENCY PER BLOCK/SLAB**  
 somewhat consistent

**WEIGHT CALCULATED IN INCHES**  
 $l \times w \times h / 1728$  (inches cubed)  $\times 176$  = approx 176 pounds per cubic foot

**ASTM TESTING DATA**  
 MILL CREEK C97 water absorption—0.51%  
 MILL CREEK C97 density—172.6 pcf  
 MILL CREEK C99  
 modulus of rupture perpendicular —2,280 psi  
 modulus of rupture parallel —860 psi  
 MILL CREEK C170  
 compressive strength—28,100 psi  
 MILL CREEK C880 flexural strength—1,580 psi

**THERMALLED**



**ARCHITECT/DESIGNER INFO**  
**MATERIAL BANK**

SKU: SM09003



**BIM DETAILS**

Revit, Hatch Patterns,  
 Seamless Textures, 3-Part  
 Specs, DWGS, SDS,  
 Warranty



**CUT STONE**  
**MILL CREEK**  
**PANELS, CUT STONE**  
**& SLABS**

