

CUT STONE

BUFF GRAY CHILTON PANELS



GEOLOGY: limestone

BASIC USE

unlimited cut stone applications including:
panels, hearths and mantels, pier caps, sills,
and custom items for specific needs

COLOR RANGE

shades of gray, blue,
buff, cream, and brown

COLOR CONSISTENCY PER PALLET

somewhat consistent

WEIGHT CALCULATED IN INCHES

$l \times w \times h / 1728$ (inches cubed) $\times 170$
= approx 170 pounds per cubic foot

PALLET

LBS / PALLET: as specified per order

RECOMMENDED FINISH OPTIONS

natural



STONE PANELS

BUFF GRAY COVERAGES

coverages calculated per custom fabrication

CUSTOM CUT TO SPEC

sawn to specified height and length for easy
installation; with installation similar to a CMU

ASTM TESTING DATA

BUFF GRAY

BUFF GRAY C97 water absorption—0.08%

BUFF GRAY C97 density—177.4 pcf

BUFF GRAY C99

modulus of rupture—1,220 psi

BUFF GRAY C170

compressive strength w/rift—50,560 psi

compressive strength across rift—38,090 psi

BUFF GRAY C880 flexural strength—3,070 psi

STONE PANELS

BUFF GRAY

TYPICAL PIECE

ends square; all sides sawn; stone shape(s)
and finishing to be specified per order

DIMENSIONS EXAMPLE

US: inches

l: 23-5/8"

h: 11-5/8"

w: 3" to 5"

METRIC: mm

l: 600 mm

h: 295 mm

w: 76 to 127 mm

note: dimensions example per image at top



www.buechelstone.com