

CUT STONE

CHANTILLY LACE (COLOR RANGES)



GEOLOGY: limestone

BASIC USE

unlimited cut stone applications including: panels, hearths and mantels, pier caps, sills, and custom items for specific needs

COLOR RANGE

yellow, cream to slight buff, mottled with occasional fossils; swirls are common

COLOR CONSISTENCY PER PALLET

somewhat consistent

WEIGHT CALCULATED IN INCHES



l x w x h / 1728 (inches cubed) x 170
= approx 170 pounds per cubic foot

PALLET

LBS / PALLET: as specified per order

RECOMMENDED FINISH OPTIONS

sawn; sand; sandblast; bushhammer; rock-face; eased edge; bullnose; and brushed.



COMMON APPLICATIONS

CHANTILLY LACE

ACCESSORIES

accent pieces (e.g. quoins, keystones, light mounts) custom cut to project requirements

BALUSTERS & COLUMNS

custom cut per project with large stone lathe

DOOR & WINDOW SURROUNDS

basic and ornate options custom cut to spec; CAD shop dwgs available for job site approval

FIREPLACE SURROUNDS

standard and custom options; CAD dwgs available for job site approval; can be used stand alone and with stone or brick fireplaces

HEARTHES & MANTELS

CHANTILLY LACE

HEARTHES & MANTELS

large selection of custom sizes available; wide range of colors and finishes; can be custom made for specific needs

STANDARD DIMENSIONS EXAMPLE

US: inches & feet	METRIC: mm & m
l: 6' (maximum)	l: 1-3/4 m (maximum)
h: 2-1/4" (standard)	h: 57 mm (standard)
d: as specified	d: as specified
note: radius available if specified	

TYPICAL PIECE

stone shape and finishing of face/ends to be specified per order

PIER CAPS & SILLS

CHANTILLY LACE

PIER CAPS

large selection of standard and custom sizes available; wide range of colors and finishes; can be custom made for specific needs

TYPICAL PIECE

ends square; stone shape(s) and finishing to be specified per order

SILLS

large selection of standard and custom sizes available; wide range of colors and finishes; can be custom made for specific needs

STANDARD DIMENSIONS EXAMPLE

US: inches & feet	METRIC: mm & m
l: 6' & l: 4' (maximum)	l: 1-3/4 m & l: 1-1/4 m
h: 2-1/4" (standard)	h: 57 mm (standard)
d: 5-1/2" & d: 2-1/2"	d: 140 mm & d: 63 mm
note: max recommended lengths are general rules of thumb for 5-1/2" & 2-1/2" depths	

TYPICAL PIECE

ends square; stone shape(s) and finishing to be specified per order

ASTM TESTING DATA

CHANTILLY LACE C97

water absorption—5.0%

CHANTILLY LACE C97 density—140.4 pcf

CHANTILLY LACE C99 modulus of rupture

perpendicular—870 psi

parallel—730 psi

CHANTILLY LACE C170

compressive strength—7,560 psi



www.buechelstone.com