

STEPS

FOND DU LAC OUTCROPPING STEPS



GEOLOGY: dolomitic limestone

BASIC USE

for steps

COLOR RANGE

gray, light gray to white, buff

COLOR CONSISTENCY PER PALLET

somewhat consistent

WEIGHT CALCULATED IN INCHES

$l \times w \times h / 1728$ (inches cubed) $\times 170$
= approx 170 pounds per cubic foot

PALLET

4,000 pounds



OUTCROPPING STEPS

COVERAGES

coverages calculated as specified per project

FOND DU LAC OUTCROPPING STEPS

DIMENSIONS

US: inches

l: 18" to 60"

h: 5" to 8"

w: 18" to 60"

note: lengths and widths are irregular shapes

18 inches to 60 inches in diameter

METRIC: mm

l: 457 to 1524 mm

h: 127 to 203 mm

w: 457 to 1524 mm

PART NUMBERS

part number: 1OUTBUE02006TN

OUTCROPPING STEPS

FOND DU LAC OUTCROPPING STEPS

TYPICAL PIECE

ends irregular;

natural cleft top and bottom;

natural split sides;

stone is somewhat square but
may be irregular

ASTM TESTING DATA

FOND DU LAC C97 water absorption—0.36%

FOND DU LAC C97 density—174.2 pcf

FOND DU LAC C99

modulus of rupture—1,470 psi

FOND DU LAC C170

compressive strength w/rift—29,040 psi

compressive strength across rift—34,240 psi

FOND DU LAC C880

flexural strength—1,740 psi



www.buechelstone.com