



## OUTCROPPINGS

### JUTE CLOTH OUTCROPPINGS

**GEOLOGY:** limestone

#### BASIC USE

for retaining ground or  
as an accent in landscaping

#### COLOR RANGE

light gray to buff with  
occasional blue veins

#### COLOR CONSISTENCY PER PALLET

somewhat consistent

#### WEIGHT CALCULATED IN INCHES

$l \times w \times h / 1728$  (inches cubed)  $\times 125.1$   
= approx 125.1 pounds per cubic foot

#### PALLET

3,000 - 4,000 pounds

## OUTCROPPINGS

### COVERAGES

coverages calculated as specified per project

### JUTE CLOTH OUTCROPPINGS

#### DIMENSIONS

US: inches

l: 18" to 60"

h: 5" to 10"

w: 18" to 60"

METRIC: mm

l: 457 to 1524 mm

h: 127 to 254 mm

w: 457 to 1524 mm

## PART NUMBERS

part number: 1OUTKNS03001TN

## OUTCROPPINGS

### JUTE CLOTH OUTCROPPINGS

#### TYPICAL PIECE

ends irregular;

natural cleft top and bottom;

natural split, seamface, or weatheredge sides;

stone is random shapes

## ASTM TESTING DATA

JUTE CLOTH C97 water absorption—10.03%

specific gravity — 1.995 to 2.008

density—125.1 lbs/ft<sup>3</sup>

#### JUTE CLOTH C170

dry perpendicular—4,040 psi

wet perpendicular—1,830 psi

dry parallel —3,210 psi

wet parallel—1,480 psi

#### JUTE CLOTH C880

flexural strength -wet —440 psi

flexural strength -dry —600 psi

