



MOSAIC
OILED NUBUCK
FIELDSTONE

GEOLOGY: limestone

BASIC USE

exterior walls of buildings and fireplaces
 stone shall be mortared in

COLOR RANGE

buff, brown, tans, gray and black

COLOR CONSISTENCY PER PALLET

somewhat consistent

WEIGHT CALCULATED IN INCHES

$l \times w \times h / 1728$ (inches cubed) x 165
 = approx 165 pounds per cubic foot

PALLET

FULL VENEER: 4,000 pounds
 THIN VENEER: 10-15 lbs/ft²; Qty Bx or Sm Bx
 Qty Bx- 100 sq ft flats and 50 lineal ft corners
 Sm Bx- (24) 8 sq ft flats (192 sq ft) and
 (20) 8 lineal ft corners (160 lineal ft)

FULL VENEER

COMMON COVERAGE *Est.(can vary)

Standard Joint	Drystack	Overgrout
40 square feet / ton	30 ft ² /ton	50 ft ² /ton

OILED NUBUCK FIELDSTONE

DIMENSIONS

US: inches (average)	METRIC: mm (average)
l: 3" to 12" dia.	l: 76 to 304 dia.
h: 3" to 12" dia.	h: 76 to 304 dia.
w: 3" to 6" (4")	w: 76 to 152 (101)

note: lengths and heights are irregular shapes
 3 inches to 12 inches in diameter

TYPICAL PIECE

ends irregular;
 natural split and rounded sides;
 bedface face and back;
 stone is random shapes

PART NUMBERS

FULL VENEER

part number: 1BSTKNS01009TN

THIN VENEER

qty bx flat: 1BTBKNS01009QB
 sm bx flat: 1BTVKNS01009BX
 qty bx corner: 1BTVKNS01509QB
 sm bx corner: 1BTVKNS01509BX

THIN VENEER

COMMON COVERAGE PER BOX *Est.(can vary)

Standard Joint	Drystack	Overgrout
8 & 100 square feet	6 & 75 ft ²	10 & 110 ft ²

OILED NUBUCK FIELDSTONE

DIMENSIONS

US: inches (average)	METRIC: mm (average)
l: 3" to 12" dia.	l: 76 to 304 dia.
h: 3" to 12" dia.	h: 76 to 304 dia.
w: 3/4" to 1-1/4" (1")	w: 19 to 31 (25)

corner return 3" to 5" cr: 76 to 127
 note: lengths and heights are irregular shapes
 3 inches to 12 inches in diameter

TYPICAL PIECE

ends irregular;
 natural split and rounded sides;
 bedface face and sawn back;
 stone is random shapes

ASTM TESTING DATA

C97 water absorption—7.27%
 C97 density—134.1 pcf
 C97 specific gravity—2.149
 C99 modulus of rupture—1,174 psi
 C170 compressive strength—6,631 psi
 C241 abrasion resistance—5.38



www.buechelstone.com