



FIELDLEDGE

**AUTUMN
SIENA**

GEOLOGY: quartzitic sandstone- quarried in USA

COLOR RANGE

buff, gray to black, orange, pink, and cream with swirls, burnt browns

COLOR CONSISTENCY PER PALLET

somewhat consistent

PALLET

FULL VENEER: 4,000 pounds
 THIN VENEER: 10-15 lbs/ft²; Qty Bx or Sm Bx
 Qty Bx-100 sq ft flats and 50 lineal ft corners
 Sm Bx- (24) 8 sq ft flats (192 sq ft) and
 (20) 8 lineal ft corners (160 lineal ft)

ASTM TESTING DATA

AUTUMN SIENA C97
 water absorption—1.92%
AUTUMN SIENA C97 density—156.0 pcf
AUTUMN SIENA C97
 specific gravity—2.495
AUTUMN SIENA C170
 compressive strength—16,550 psi
AUTUMN SIENA C880
 flexural strength—1,580 psi

PART NUMBERS

FULL VENEER:

1BSTTEN01004TN - Sold per Ton

THIN VENEER:

Qty Bx flat: 1BTVTEN01004QB- Sold per pallet
 Sm Bx flat: 1BTVTEN01004BX - Sold per box
 Qty Bx corner: 1BTVTEN01504QB- Sold per pallet
 Sm Bx corner: 1BTVTEN01504BX - Sold per box

FULL VENEER

COMMON COVERAGE ^{*Est.(can vary)}		
Standard Joint	Drystack	Overgrout
40 square feet / ton	30 ft ² /ton	50 ft ² /ton

DIMENSIONS

l: 4" to 16"
 h: 2" to 8"
 w: 3" to 5" (4")

TYPICAL BLEND

10 percent installed bedface out;
 stone is snapped at least one face;
 sides may or may not be squared;
 overall appearance of stone will be linear
 when installed

TYPICAL PIECE

Ends square; sawn top and bottom; sides
 are split; split face and back with occasional
 bedface; stone is rectangular in appearance
 with length longer than height.

THIN VENEER

COMMON COVERAGE PER BOX ^{*Est.(can vary)}		
Standard Joint	Drystack	Overgrout
8 & 100 square feet	6 & 75 ft ²	10 & 110 ft ²

DIMENSIONS

l: 4" to 16"
 h: 2" to 8"
 w: 3/4" to 1-1/4" (1")
 corner return 3" to 5"

TYPICAL BLEND

10 percent installed bedface out;
 stone is snapped at least one face;
 sides may or may not be squared;
 overall appearance of stone will be linear
 when installed

TYPICAL PIECE

ends random;
 natural cleft top and bottom;
 split or natural split face and sawn back;
 most sides more irregular and not square

ARCHITECT/DESIGNER INFO

MATERIAL BANK

SKU: SM04001



INSTALLATION SHOWN

Mortar: Laticrete MVIS
 Joint Type: Drystack

BIM DETAILS

Revit, Hatch Patterns,
 Seamless Textures, 3-Part
 Specs, DWGS, SDS,
 Warranty

