# **ASHLAR**

# CHILTON COUNTRY SQUIRE



**GEOLOGY**: dolomitic limestone- quarried in USA

#### **COLOR RANGE**

gray to charcoal, with occasional mauves

## **COLOR CONSISTENCY PER PALLET**

consistent

#### **PALLET**

FULL VENEER: 4,000 pounds
THIN VENEER: 10-15 lbs/ft²; Qty Bx or Sm Bx
Qty Bx- 100 sq ft flats and 50 lineal ft corners
Sm Bx- (24) 8 sq ft flats (192 sq ft) and
(20) 8 lineal ft corners (160 lineal ft)

### **ASTM TESTING DATA**

CHILTON C97 water absorption—0.08%
CHILTON C97 density—177.4 pcf
CHILTON C99 modulus of rupture—1,220 psi
CHILTON C170

compressive strength w/rift—50,560 psi compressive strength across rift—38,090 psi CHILTON C880 flexural strength—3,070 psi

# **PART NUMBER**

## FULL VENEER:

1BSTBUE01003TN - Sold per Ton

#### THIN VENEER:

Qty Bx flat: 1BTVBUE01002QB- Sold per pallet Sm Bx flat: 1BTVBUE01002BX - Sold per box Qty Bx corner: 1BTVBUE01502QB- Sold per pallet Sm Bx corner: 1BTVBUE01502BX- Sold per box

# ARCHITECT/DESIGNER INFO

# MATERIAL BANK

SKU: SM01006



# INSTALLATION SHOWN

Mortar: Laticrete- Std. Gray Joint Type: Raked

# **BIM DETAILS**

Revit, Hatch Patterns, Seamless Textures, 3-Part Specs, DWGS, SDS, Warranty



# FULL VENEER

## COMMON COVERAGE \*Est.(can vary)

Standard Joint Drystack Overgrout 40 square feet / ton 30 ft²/ton 50 ft²/ton DIMENSIONS

l: 6" to 42" (14") h: 1/2" to 8" w: 3" to 5" (4")

Stone Ends shall be no less than 2-1/2" width TYPICAL PIECE

Ends square, natural cleft top and bottom. Back, face and sides split. Rectangular in appreance.

# THIN VENEER

# COMMON COVERAGE PER BOX \*Est.(can vary)

Standard Joint Drystack Overgrout 8 & 100 square feet 6 & 75 ft<sup>2</sup> 10 & 110 ft<sup>2</sup> DIMENSIONS

l: 6" to 24" (12") h: 1/2" to 8" w: 3/4" to 1-1/4" (1") corner return 3" to 5" TYPICAL PIECE

Ends square, natural cleft top and bottom. Face and sides split, back is sawn. Rectangular in appearance.



