

### FULL VENEER

Standard JointDrystackOvergrout40 square feet / ton30 ft²/ton50 ft²/ton

\*Est.(can vary)

DIMENSIONS I: 6" to 42" (16")

h: 1/2" to 8"

w: 3" to 5" (4")

Stone ends shall be no less than 2-1/2" width TYPICAL PIECE \_\_\_\_\_

Ends somewhat square, natural cleft top and bottom. Back, and sides split, face weatheredge & seamface. Stone is rectangular.

## THIN VENEER

COMMON COVERAGE PER BOX Standard Joint Drystack Overgrout 8 & 100 square feet 6 & 75 ft<sup>2</sup> 10 & 110 ft<sup>2</sup> DIMENSIONS I: 6" to 24" (12") h: 1/2" to 8" w: 3/4" to 1-1/4" (1") corner return 3" to 5" TYPICAL PIECE Ends somewhat square; natural cleft top & bottom; sides split, face weatheredge & seamface; sawn back. Stone is rectangular.



# ASHLAR CHILTON RUSTIC NO RED

**GEOLOGY**: dolomitic limestone- quarried in USA

#### COLOR RANGE

brown, buff, orange, yellow, and rust

COLOR CONSISTENCY PER PALLET somewhat consistent

#### PALLET

FULL VENEER: 4,000 pounds THIN VENEER: 10-15 lbs/ft<sup>2</sup>; Qty Bx or Sm Bx Qty Bx-100 sq ft flats and 50 lineal ft corners Sm Bx- (24) 8 sq ft flats (192 sq ft) and (20) 8 lineal ft corners (160 lineal ft)

#### ASTM TESTING DATA

CHILTON C97 water absorption—0.08% CHILTON C97 density—177.4 pcf CHILTON C99 modulus of rupture—1,220 psi CHILTON C170 compressive strength w/rift—50,560 psi compressive strength across rift—38,090 psi CHILTON C880 flexural strength—3,070 psi

## PART NUMBERS

FULL VENEER: 1BSTBUE01031TN- Sold per Ton

THIN VENEER: Qty Bx flat: 1BTVBUE01032QB - Sold per pallet Sm Bx flat: 1BTVBUE01032BX- Sold per box Qty Bx corner: 1BTVBUE01533QB- Sold per pallet Sm Bx corner: 1BTVBUE01533BX- Sold per box

# ARCHITECT/DESIGNER INFO

SKU: SM01011



# INSTALLATION SHOWN

Mortar: Western W-11 Joint Type: Raked

BIM DETAILS Revit, Hatch Patterns, Seamless Textures, 3-Part Specs, DWGS, SDS, Warranty



