

# **FULL VENEER**

COMMON COVERAGE

\*Est.(can vary)

Drystack Standard Joint Overgrout 40 square feet / ton 30 ft²/ton 50 ft2/ton **DIMENSIONS** 

I: 6" to 24" (12") h: 2-1/4"; h: 5";

h: 7-3/4"

w: 3" to 5" (4")

note: ± 1/8" on sawn heights

TYPICAL BLEND

33.33 percent 2-1/4"; 33.33 percent 5";

33.33 percent 7-3/4"

TYPICAL PIECE

Ends square; all sides sawn; stone is rectangular having linear sawn appearance with length longer than height.

# THIN VENEER

COMMON COVERAGE PER BOX

Standard Joint Drystack Overgrout 8 & 100 square feet 6 & 75 ft<sup>2</sup> 10 & 110 ft<sup>2</sup> DIMENSIONS

I: 6" to 24" (12") h: 2-1/4"; h: 5";

h: 7-3/4"

w: 3/4" to 1-1/4" (1") corner return 3" to 5"

note: ± 1/8" on sawn heights

TYPICAL BLEND

33.33 percent 2-1/4"; 33.33 percent 5";

33.33 percent 7-3/4"

TYPICAL PIECE

Ends square; all sides sawn;

stone is rectangular having linear sawn appearance with length longer than height.



# DIMENSIONAL

**CHILTON SHABBY-CHIC TAILORED BLEND** 

GEOLOGY: dolomitic limestone- quarried in USA

#### **COLOR RANGE**

gray to charcoal, and mauves

#### COLOR CONSISTENCY PER PALLET

somewhat consistent

FULL VENEER: 4,000 pounds

THIN VENEER: 10-15 lbs/ft2; Qty Bx or Sm Bx Qty Bx-100 sq ft flats and 50 lineal ft corners Sm Bx- (24) 8 sq ft flats (192 sq ft) and (20) 8 lineal ft corners (160 lineal ft)

#### **ASTM TESTING DATA**

CHILTON C97 water absorption—0.08% CHILTON C97 density-177.4 pcf CHILTON C99 modulus of rupture-1,220 psi CHILTON C170

compressive strength w/rift-50,560 psi compressive strength across rift—38,090 psi CHILTON C880 flexural strength—3,070 psi

# PART NUMBERS

**FULL VENEER:** 

1BSTBUE01070TN- Sold per Ton

#### THIN VENEER:

Qty Bx flat: 1BTVBUE01070QB- Sold per pallet Sm Bx flat: 1BTVBUE01070BX- Sold per box Qty Bx corner: 1BTVBUE01750QB- Sold per pallet Sm Bx corner: 1BTVBUE01750BX- Sold per box

# ARCHITECT/DESIGNER

MATERIAL BANK

SKU: SM03002



### INSTALLATION SHOWN

Mortar: Western W-5 (White) Joint Type: Raked

#### BIM DETAILS

Revit, Hatch Patterns, Seamless Textures, 3-Part Specs, DWGS, SDS, Warranty



