

COMMON COVERAGE

Standard Joint Drystack Overgrout 40 square feet / ton 30 ft²/ton 50 ft2/ton **DIMENSIONS**

I: 6" to 24" (12") h: 1/2" to 8" w: 3" to 5" (4")

Stone ends shall be no less than 2-1/2" width TYPICAL PIECE

Ends somewhat square, natural cleft top and bottom. Back, face, and sides split. Stone is mostly rectangular. Tumbled rounded edges.

THIN VENEER

COMMON COVERAGE PER BOX

Drystack Overgrout Standard Joint 8 & 100 square feet 6 & 75 ft² 10 & 110 ft² **DIMENSIONS**

I: 6" to 24" (12") h: 1/2" to 8" w: 3/4" to 1-1/4" (1") corner return 3" to 5" TYPICAL PIECE

Ends somewhat square; natural cleft top & bottom; sides and face split; sawn back. Stone is mostly rectangular. Tumbled rounded edges.



ASHLAR COLONIAL GRAY RIVER ROCK

GEOLOGY: dolomitic limestone- quarried

COLOR RANGE

tumbled Chilton Country Squire white from tumbling

COLOR CONSISTENCY PER PALLET consistent

PALLET

FULL VENEER: 4,000 pounds THIN VENEER: 10-15 lbs/ft2; Qty Bx or Sm Bx Qty Bx-100 sq ft flats and 50 lineal ft corners Sm Bx- (24) 8 sq ft flats (192 sq ft) and (20) 8 lineal ft corners (160 lineal ft)

ASTM TESTING DATA

CHILTON C97 water absorption—0.08% CHILTON C97 density-177.4 pcf CHILTON C99 modulus of rupture-1,220 psi CHILTON C170

compressive strength w/rift-50,560 psi compressive strength across rift—38,090 psi CHILTON C880 flexural strength—3,070 psi

PART NUMBERS

FULL VENEER:

1BSTBUE01503TN - Sold per Ton

THIN VENEER:

Qty Bx flat: 1BTVBUE01011QB - Sold per pallet Sm Bx flat: 1BTVBUE01011BX- Sold per box Qty Bx corner: 1BTVBUE01511QB- Sold per pallet Sm Bx corner: 1BTVBUE01511BX- Sold per

MATERIAL BANK

SKU: SM01013



INSTALLATION SHOWN

Mortar: Laticrete- Std. Gray Joint Type: Raked

BIM DETAILS

Revit, Hatch Patterns, Seamless Textures, 3-Part Specs, DWGS, SDS, Warranty





14 ASHLAR LINE 2022 STONE SPECIFICATIONS www.buechelstone.com