



CASTLE ROCK
FOND DU LAC
CASTLE ROCK

GEOLOGY: dolomitic limestone- quarried in USA

COLOR RANGE
 gray, light gray, tan, buff, and white

COLOR CONSISTENCY PER PALLET
 somewhat consistent

PALLET
 FULL VENEER: 4,000 pounds
 THIN VENEER: 10-15 lbs/ft²; Qty Bx or Sm Bx
 Qty Bx-100 sq ft flats and 50 lineal ft corners
 Sm Bx- (24) 8 sq ft flats (192 sq ft) and
 (20) 8 lineal ft corners (160 lineal ft)

ASTM TESTING DATA
 FOND DU LAC C97 water absorption—0.11%
 FOND DU LAC C97 density—176.5 pcf
 FOND DU LAC C99
 modulus of rupture—2,480 psi
 FOND DU LAC C170
 compressive strength w/rift—31,810 psi
 compressive strength across rift—26,550 psi
 FOND DU LAC C880
 flexural strength—1,740 psi

PART NUMBERS

FULL VENEER:
 1BSTBUE02007TN- Sold per Ton
THIN VENEER:
 Qty Bx flat: 1BTVBUE02007QB- Sold per pallet
 Sm Bx flat: 1BTVBUE02007BX- Sold per box
 Qty Bx corner: 1BTVBUE02507QB- Sold per pallet
 Sm Bx corner: 1BTVBUE02507BX- Sold per box

FULL VENEER

COMMON COVERAGE *Est.(can vary)

Standard Joint	Drystack	Overgrout
40 square feet / ton	30 ft ² /ton	50 ft ² /ton

DIMENSIONS
 l: 6" to 42" (16")
 h: 4" to 12"
 w: 3" to 5" (4")
 Stone ends shall be no less than 2-1/2" width
TYPICAL PIECE
 Ends square; split top, bottom, and sides;
 bedface face and back;stone is squares and rectangles.

THIN VENEER

COMMON COVERAGE PER BOX *Est.(can vary)

Standard Joint	Drystack	Overgrout
8 & 100 square feet	6 & 75 ft ²	10 & 110 ft ²

DIMENSIONS
 l: 6" to 24" (12")
 h: 4" to 12"
 w: 3/4" to 1-1/4" (1")
 corner return 3" to 5"
TYPICAL PIECE
 Ends square; split top, bottom, and sides;
 bedface face and sawn back;
 stone is squares and rectangle.

ARCHITECT/DESIGNER INFO

MATERIAL BANK
 SKU: SM02006 

INSTALLATION SHOWN

Mortar: Western Type S
 Joint Type: Raked

BIM DETAILS

Revit, Hatch Patterns,
 Seamless Textures, 3-Part
 Specs, DWGS, SDS,
 Warranty 

