

## **FULL VENEER**

## **COMMON COVERAGE**

\*Est.(can vary)

Standard Joint Drystack Overgrout 40 square feet / ton 30 ft²/ton 50 ft2/ton **DIMENSIONS** 

I: 6" to 42" (24") h: 2-1/4"; h: 5"; h: 7-3/4"; h: 10-1/2" w: 3" to 5" (4")

note: ± 1/8" on sawn heights - additional heights avaliable

TYPICAL BLEND

20 percent 2-1/4"; 40 percent 5"; 30 percent 7-3/4"; 10 percent 10-1/2" TYPICAL PIECE

Ends square; sawn top and bottom; sides are split; bedface face and back; stone is rectangular in appearance with length longer than height.

## THIN VENEER

## COMMON COVERAGE PER BOX

Standard Joint Drystack Overgrout 8 & 100 square feet 6 & 75 ft<sup>2</sup> 10 & 110 ft<sup>2</sup> DIMENSIONS

I: 6" to 24" (12") h: 2-1/4"; h: 5"; h: 7-3/4"; h: 10-1/2" w: 3/4" to 1-1/4" (1") corner return 3" to 5"

note: ± 1/8" on sawn heights- additional heights available

TYPICAL BLEND

20 percent 2-1/4"; 40 percent 5"; 30 percent 7-3/4"; 10 percent 10-1/2" TYPICAL PIECE

Ends square; sawn top and bottom; sides are split: bedface face and sawn back: stone is rectangular in appearance with length longer than height.



# DIMENSIONAL

## **FOND DU LAC TAILORED BLEND**

**GEOLOGY**: dolomitic limestone- quarried in USA

#### **COLOR RANGE**

gray, light gray, buff, and white

#### COLOR CONSISTENCY PER PALLET

somewhat consistent

#### **PALLET**

FULL VENEER: 4,000 pounds

THIN VENEER: 10-15 lbs/ft2; Qty Bx or Sm Bx Qty Bx-100 sq ft flats and 50 lineal ft corners Sm Bx- (24) 8 sq ft flats (192 sq ft) and (20) 8 lineal ft corners (160 lineal ft)

#### **ASTM TESTING DATA**

flexural strength - 1,740 psi

FOND DU LAC C97 water absorption—0.11% FOND DU LAC C97 density—176.5 pcf FOND DU LAC C99 modulus of rupture—2,480 psi FOND DU LAC C170 compressive strength w/rift-31,810 psi compressive strength across rift—26,550 psi FOND DU LAC C880

## PART NUMBERS

**FULL VENEER:** 

1BSTBUE02009TN - Sold per Ton

#### THIN VENEER:

Qty Bx flat: 1BTVBUE02006QB- Sold per pallet Sm Bx flat: 1BTVBUE02006BX- Sold per box Qty Bx corner: 1BTVBUE02506QB- Sold per pallet Sm Bx corner: 1BTVBUE02506BX- Sold per box

## ARCHITECT/DESIGNER

#### MATERIAL BANK

SKU: SM03006



## INSTALLATION SHOWN

Mortar: Laticrete- Std. Gray Joint Type: Raked

## BIM DETAILS

Revit, Hatch Patterns, Seamless Textures, 3-Part Specs, DWGS, SDS, Warranty



