

# TAILORED FIELDLEDGE



FOND DU LAC

## TAILORED FIELDLEDGE

**GEOLOGY:** dolomitic limestone- quarried in USA

### COLOR RANGE

grays, light grays, buffs, and whites

### COLOR CONSISTENCY PER PALLET

somewhat consistent

### PALLET

FULL VENEER: N/A

THIN VENEER: 10-15 lbs/ft<sup>2</sup>; Qty Bx or Sm Bx  
Qty Bx- 100 sq ft flats and 50 lineal ft corners  
Sm Bx- (24) 8 sq ft flats (192 sq ft) and  
(20) 8 lineal ft corners (160 lineal ft)

## ASTM TESTING DATA

FOND DU LAC C97 water absorption—0.11%

FOND DU LAC C97 density—176.5 pcf

FOND DU LAC C99

modulus of rupture—2,480 psi

FOND DU LAC C170

compressive strength w/rift—31,810 psi

compressive strength across rift—26,550 psi

FOND DU LAC C880

flexural strength—1,740 psi



## PART NUMBER

FULL VENEER:

N/A

THIN VENEER:

Qty Bx flat: 1BTVBUE02071QB- Sold per pallet

Sm Bx flat: 1BTVBUE02071BX- Sold per box

Qty Bx corner: 1BTVBUE02571QB - Sold per pallet

Sm Bx corner: 1BTVBUE02571BX- Sold per box

## ARCHITECT/DESIGNER INFO

### MATERIAL BANK

SKU: SM07004



## INSTALLATION SHOWN

Mortar: Laticrete MVIS

Joint Type: Drystack

## BIM DETAILS

Revit, Hatch Patterns,  
Seamless Textures, 3-Part  
Specs, DWGS, SDS,  
Warranty



## THIN VENEER

### COMMON COVERAGE PER BOX <sup>\*Est.(can vary)</sup>

Figured for Drystacked Joint Only  
8 & 100 square feet

### DIMENSIONS

l: 3" to 24" (8")

h: 2"; h: 4"; h: 6"

w: 3/4" to 1-1/4" (1")

corner return N/A- Butt Jointed

note: sawn heights with varying lengths  
having rough irregular ends

### TYPICAL PIECE

Ends irregular; random lengths;  
sawn top and bottom; sides not square;  
bedface and split face and sawn back;  
overall appearance of stone will be linear  
when installed.

SEE CORNER EXAMPLE TO THE LEFT