

COMMON COVERAGE

Standard Joint Drystack Overgrout 40 square feet / ton 30 ft²/ton 50 ft2/ton **DIMENSIONS**

l: 4" to 16" h: 2" to 8"

w: 3" to 5" (4")

note: product can vary in height from full height to half the total height in one piece TYPICAL BLEND

10 percent installed bedface out; stone is snapped at least one face; sides may or may not be squared; overall appearance of stone will be linear when installed

TYPICAL PIECE

Ends random; natural cleft top and bottom; split or natural split face, split back; most sides more irregular and not square.

COMMON COVERAGE PER BOX

Standard Joint Drystack Overgrout 8 & 100 square feet 6 & 75 ft² 10 & 110 ft² DIMENSIONS

I: 4" to 16" h: 2" to 8"

w: 3/4" to 1-1/4" (1") corner return 3" to 6"

note: product can vary in height from full height to half the total height in one piece TYPICAL BLEND

10 percent installed bedface out; stone is snapped at least one face; sides may or may not be squared; overall appearance of stone will be linear when installed TYPICAL PIECE

Ends random; natural cleft top and bottom; split or natural split face and sawn back; most sides more irregular and not square.



FIELDLEDGE MILL CREEK

SIENA

GEOLOGY: dolomitic limestone- quarried in USA

COLOR RANGE

light gray to buff with occasional blue veins

COLOR CONSISTENCY PER PALLET

somewhat consistent

PALLET

FULL VENEER: 4,000 pounds

THIN VENEER: 10-15 lbs/ft²; Qty Bx or Sm Bx Qty Bx-100 sq ft flats and 50 lineal ft corners Sm Bx- (24) 8 sq ft flats (192 sq ft) and (20) 8 lineal ft corners (160 lineal ft)

ASTM TESTING DATA

MILL CREEK C97 water absorption—0.51% MILL CREEK C97 density-172.6 pcf MILL CREEK C99 modulus of rupture perpendicular -2,280 psi

modulus of rupture parallel -860 psi MILL CREEK C170

compressive strength-28,100 psi

MILL CREEK C880 flexural strength-1,580 psi

PART NUMBERS

FULL VENEER:

1BSTLEN01016TN- Sold per Ton

THIN VENEER:

Qty Bx flat: 1BTVLEN01016QB - Sold per pallet Sm Bx flat: 1BTVLEN01016BX- Sold per box Qty Bx corner: 1BTVLEN01516QB- Sold per pallet Sm Bx corner: 1BTVLEN01516BX - Sold per box

ARCHITECT/DESIGN

MATERIAL BANK

SKU: SM04008



INSTALLATION SHOWN

Mortar: Laticrete MVIS Joint Type: Drystack

BIM DETAILS

Revit, Hatch Patterns, Seamless Textures, 3-Part Specs, DWGS, SDS, Warranty



