



MOSAIC
MILL CREEK
WEBWALL

GEOLOGY: dolomitic limestone - quarried in USA

COLOR RANGE

brown to buff with occasional gray

COLOR CONSISTENCY PER PALLET

consistent

PALLET

FULL VENEER: 4,000 pounds
THIN VENEER: 10-15 lbs/ft²; Qty Bx or Sm Bx
Qty Bx-100 sq ft flats and 50 lineal ft corners
Sm Bx- (24) 8 sq ft flats (192 sq ft) and
(20) 8 lineal ft corners (160 lineal ft)

ASTM TESTING DATA

MILL CREEK C97 water absorption—0.51%
MILL CREEK C97 density—172.6 pcf
MILL CREEK C99
modulus of rupture perpendicular —2,280 psi
modulus of rupture parallel —860 psi
MILL CREEK C170
compressive strength—28,100 psi
MILL CREEK C880 flexural strength—1,580 psi

PART NUMBERS

FULL VENEER:

1BSTLEN01007TN- Sold per Ton

THIN VENEER:

Qty Bx flat: 1BTVLEN01006QB - Sold per pallet
Sm Bx flat: 1BTVLEN01006BX - Sold per box
Qty Bx corner: 1BTVLEN01506QB - Sold per pallet
Sm Bx corner: 1BTVLEN01506BX - Sold per box

FULL VENEER

COMMON COVERAGE *Est.(can vary)

Standard Joint	Drystack	Overgrout
40 square feet / ton	30 ft ² /ton	50 ft ² /ton

DIMENSIONS

l: 3" to 16" dia.
h: 3" to 16" dia.
w: 3" to 5" (4")
note: lengths and heights are irregular shapes
3 inches to 16 inches in diameter

TYPICAL PIECE

Ends irregular; natural split sides; bedface face and back; stone is random shapes.

THIN VENEER

COMMON COVERAGE PER BOX *Est.(can vary)

Standard Joint	Drystack	Overgrout
8 & 100 square feet	6 & 75 ft ²	10 & 110 ft ²

DIMENSIONS

l: 3" to 12" dia.
h: 3" to 12" dia.
w: 3/4" to 1-1/4" (1")
corner return 3" to 6"
note: lengths and heights are irregular shapes
3 inches to 12 inches in diameter

TYPICAL PIECE

Ends irregular; natural split sides; bedface face and sawn back; stone is random shapes.

ARCHITECT/DESIGNER INFO

MATERIAL BANK

SKU: SM06015



INSTALLATION SHOWN

Mortar: Western W-11
Joint Type: Raked

BIM DETAILS

Revit, Hatch Patterns,
Seamless Textures, 3-Part
Specs, DWGS, SDS,
Warranty



www.buechelstone.com