

CASTLE ROCK

OILED NUBUCK

CASTLE ROCK



GEOLOGY: limestone - quarried in USA

COLOR RANGE

buff, brown, tans, gray and black

COLOR CONSISTENCY PER PALLET

somewhat consistent

PALLET

FULL VENEER: 4,000 pounds

THIN VENEER: 10-15 lbs/ft²; Qty Bx or Sm Bx

Qty Bx- 100 sq ft flats and 50 lineal ft corners

Sm Bx- (24) 8 sq ft flats (192 sq ft) and

(20) 8 lineal ft corners (160 lineal ft)

ASTM TESTING DATA

C97 water absorption—7.27%

C97 density—134.1 pcf

C97 specific gravity—2.149

C99 modulus of rupture—1,174 psi

C170 compressive strength—6,631 psi

C241 abrasion resistance—5.38

PART NUMBER

FULL VENEER:

1BSTKNS03011TN- Sold per Ton

THIN VENEER:

Qty Bx flat: 1BTVKNS03011QB- Sold per pallet

Sm Bx flat: 1BTVKNS03011BX- Sold per box

Qty Bx corner: 1BTVKNS03511QB- Sold per pallet

Sm Bx corner: 1BTVKNS03511BX- Sold per box

ARCHITECT/DESIGNER INFO

MATERIAL BANK

SKU: SM02016



INSTALLATION SHOWN

Mortar: Western W-11

Joint Type: Raked

BIM DETAILS

Revit, Hatch Patterns,
Seamless Textures, 3-Part
Specs, DWGS, SDS,
Warranty



FULL VENEER

COMMON COVERAGE *Est.(can vary)

Standard Joint	Drystack	Overgrout
40 square feet / ton	30 ft ² /ton	50 ft ² /ton

DIMENSIONS

l: 4" to 24" (14")

h: 4" to 12"

w: 3" to 5" (4")

Stone Ends shall be no less than 2-1/2" width

TYPICAL PIECE

Ends square; split top, bottom, and sides;
bedface and splitface face and back;
stone is squares and rectangles.

THIN VENEER

COMMON COVERAGE PER BOX *Est.(can vary)

Standard Joint	Drystack	Overgrout
8 & 100 square feet	6 & 75 ft ²	10 & 110 ft ²

DIMENSIONS

l: 4" to 24" (14")

h: 4" to 12"

w: 3/4" to 1-1/4" (1")

corner return 3" to 5"

TYPICAL PIECE

Ends square; split top, bottom, and sides;
bedface and splitface face and sawn back;
stone is squares and rectangles.