



## LEDGESTONE

SPALTED OAK  
LEDGESTONE

**GEOLOGY:** schist - quarried in USA

### COLOR RANGE

buffs, tans, golds, oranges, browns, grays, yellows, rusts, and whites with occasional burgundy and black

### COLOR CONSISTENCY PER PALLET

somewhat consistent

### PALLET

FULL VENEER: 4,000 pounds  
THIN VENEER: 10-15 lbs/ft<sup>2</sup>; Qty Bx or Sm Bx  
Qty Bx-100 sq ft flats and 50 lineal ft corners  
Sm Bx- (24) 8 sq ft flats (192 sq ft) and  
(20) 8 lineal ft corners (160 lineal ft)

### ASTM TESTING DATA

HIGHLAND SCOTCH | BARNWOOD BLUE C97  
water absorption—1.4% | 0.5%  
HIGHLAND SCOTCH | BARNWOOD BLUE C97  
specific gravity—2.54 | 2.75  
HIGHLAND SCOTCH | BARNWOOD BLUE C97  
density—158.4 pcf | 171.8 pcf  
HIGHLAND SCOTCH | BARNWOOD BLUE C99  
modulus of rupture perpendicular  
dry—2,460 psi | 3,490 psi  
modulus of rupture perpendicular  
wet—2,050 psi | 2,920 psi  
modulus of rupture parallel  
wet—1,308 psi | n/a  
HIGHLAND SCOTCH | BARNWOOD BLUE C170  
compressive strength parallel  
dry—n/a | 12,260 psi  
compressive strength parallel  
wet—14,180 psi | 9,770 psi  
compressive strength perpendicular  
wet—12,920 psi | 11,220 psi  
compressive strength perpendicular  
dry—n/a | 15,300 psi

### PART NUMBERS

#### FULL VENEER:

1BSTGRA03032TN- Sold per Ton

#### THIN VENEER:

Qty Bx flat: 1BTVGRA03032QB - Sold per pallet

Sm Bx flat: 1BTVGRA03032BX - Sold per box

Qty Bx corner: 1BTVGRA03532QB- Sold per pallet

Sm Bx corner: 1BTVGRA03532BX - Sold per box

### ARCHITECT/DESIGNER INFO

#### MATERIAL BANK

SKU: SM05010



### INSTALLATION SHOWN

Mortar: Laticrete MVIS

Joint Type: Drystack

### BIM DETAILS

Revit, Hatch Patterns,  
Seamless Textures, 3-Part  
Specs, DWGS, SDS,  
Warranty



### FULL VENEER

**COMMON COVERAGE** <sup>\*Est.(can vary)</sup>  
Standard Joint      Drystack      Overgrout  
35 square feet / ton    25 ft<sup>2</sup>/ton    45 ft<sup>2</sup>/ton

#### DIMENSIONS

l: 4" to 16" (8")

h: 1/2" to 3"

w: 3" to 5" (4")

#### TYPICAL PIECE

Ends random; Natural cleft or sawn top and bottom; natural splitface and seamface face; sides natural split or seamface; back sawn or split; stone is linear.

### THIN VENEER

**COMMON COVERAGE PER BOX** <sup>\*Est.(can vary)</sup>  
Standard Joint      Drystack      Overgrout  
8 & 100 square feet    6 & 75 ft<sup>2</sup>    10 & 110 ft<sup>2</sup>

#### DIMENSIONS

l: 4" to 16" (8")

h: 1/2" to 3"

w: 3/4" to 1-1/4" (1")

corner return 3" to 6"

#### TYPICAL PIECE

Ends random; Natural cleft or sawn top and bottom; natural splitface and seamface face; sides natural split or seamface; back sawn; stone is linear.



www.buechelstone.com