

LEDGESTONE

WHISPERING PINES LEDGESTONE



GEOLOGY: quartzitic sandstone- quarried in USA

COLOR RANGE
greens, blues, and browns

COLOR CONSISTENCY PER PALLET
somewhat consistent

PALLET
FULL VENEER: 4,000 pounds
THIN VENEER: 10-15 lbs/ft²; Qty Bx or Sm Bx
Qty Bx- 100 sq ft flats and 50 lineal ft corners
Sm Bx- (24) 8 sq ft flats (192 sq ft) and
(20) 8 lineal ft corners (160 lineal ft)

ASTM TESTING DATA

WHISPERING PINES C97
water absorption—0.96%
WHISPERING PINES C97
specific gravity—2.65
WHISPERING PINES C99
modulus of rupture—4,550 psi
WHISPERING PINES C170
compressive strength—11,630 psi
WHISPERING PINES C880
flexural strength—2,120 psi

PART NUMBER

FULL VENEER:
1BSTCAT01001TN - Sold per Ton

THIN VENEER:
Qty Bx flat: 1BTVCAT01001QB - Sold per pallet
Sm Bx flat: 1BTVCAT01001BX - Sold per box
Qty Bx corner: 1BTVCAT01501QB - Sold per pallet
Sm Bx corner: 1BTVCAT01501BX - Sold per box

ARCHITECT/DESIGNER INFO

MATERIAL BANK

SKU: SM05011



INSTALLATION SHOWN

Mortar: Laticrete MVIS
Joint Type: Drystack

BIM DETAILS

Revit, Hatch Patterns,
Seamless Textures, 3-Part
Specs, DWGS, SDS,
Warranty



FULL VENEER

COMMON COVERAGE *Est.(can vary)

Standard Joint	Drystack	Overgrout
35 square feet / ton	25 ft ² /ton	45 ft ² /ton

DIMENSIONS

l: 6" to 18" (12")
h: 1" to 4"
w: 3" to 5" (4")

TYPICAL PIECE

Ends random; natural cleft top and bottom; back, face, and sides natural split, back split or sawn; stone is linear.

THIN VENEER

COMMON COVERAGE PER BOX *Est.(can vary)

Standard Joint	Drystack	Overgrout
8 & 100 square feet	6 & 75 ft ²	10 & 110 ft ²

DIMENSIONS

l: 6" to 18" (10")
h: 1" to 4"
w: 3/4" to 1-1/4" (1")
corner return 3" to 5"

TYPICAL PIECE

Ends random; natural cleft top and bottom; back, face, and sides natural split, back sawn; stone is linear.